

- ^ Output resolution: up to 4K if HDMI only; up to 1080p if HDMI & VGA dual output
- ^ BYOD and native protocols support
- ^ 2 contents shared simultaneous on screen
- ^ Up to 8 simultaneous connections
- ^ Recommended max connection distance (ASTROS POD ↔ AS-101): 8–10 M

*ASTROS POD can be manually paired with other Wi-Fi under the same LAN as AS-101 if the distance is over 10M.*

<b>Compatible OS</b>	Windows 10+ macOS 12.5+ Chrome OS 84.0.4147.110+	Android 11.0+ iOS 14+
<b>Support protocol</b>	BeamOp, AirPlay, Google Cast, Browser Sharing, Miracast	
<b>Video output</b>	HDMI / VGA	
<b>Output resolution</b>	HDMI only: 4K@60Hz; HDMI + VGA dual output: 1080p@60Hz	
<b>Audio output</b>	HDMI & Audio Jack 3.5mm	
<b>Wi-Fi Band</b>	Switchable dual band 2.4GHZ / 5GHz (DFS channels not supported)	
<b>Wireless transmission protocol</b>	IEEE 802.11ac	
<b>Encryption protocol</b>	AP mode: WPA2-PSK Station mode: WEP, WPA, WPA2, 802.1x EAP	
<b>Ethernet</b>	10/100/1000 Mbps RJ-45 LAN	
<b>Interface</b>	1 x HDMI, 1x VGA 1 x USB 2.0 Host Type-A 1 x USB 3.0 Host Type-A 1 x USB 3.0 Host Type-C	1 x 3.5mm Audio Jack 1 x 10/100/1000 Ethernet LAN 1 x Power Jack
<b>Power supply</b>	12V 2A	
<b>Net weight</b>	500g	
<b>Dimension</b>	170mm x 104.4mm x 30.5mm (HxWxD)	
<b>Temperature</b>	Operating: 0° – 40° C (32° – 104° F) Storage: -10° – 70° C (14° – 158° F)	
<b>Humidity</b>	Operating: 20 – 80% non-condensing Storage: 10 – 90% non-condensing	
<b>Certificate</b>	FCC, CE, NCC, BSMI	

Warranty | 3 years

