

- ^ Output resolution: up to 4K if HDMI only; up to 1080p if HDMI & VGA dual output.
- ^ BYOD and native protocols support.
- ^ Supports wireless collaboration.
- ^ Supports wireless video conferencing through both software (ASTROS Windows App) and hardware (ASTROS POD).
- ^ 4 contents shared simultaneously on screen.
- ^ Up to 20 simultaneous connections.
- ^ Recommended max connection distance (ASTROS POD ↔ AS-201): 8–10 m

ASTROS POD can be manually paired with other Wi-Fi under the same LAN as AS-201 if the distance is over 10M.

Compatible OS	Windows 10+ macOS 12.5+ (BYOM 13.5+) Chrome OS 84.0.4147.110+	Android 11.0+ iOS 14+
Support protocol	BeamOp, AirPlay, Google Cast, Browser Sharing, Miracast	
Video output	HDMI / VGA	
Output resolution	HDMI only: 4K@60Hz; HDMI + VGA dual output: 1080p@60Hz	
Audio output	HDMI & Audio Jack 3.5mm	
Wi-Fi Band	Switchable dual band 2.4GHZ / 5GHZ (DFS channels not supported)	
Wireless transmission protocol	IEEE 802.11ac	
Encryption protocol	AP mode: WPA2-PSK Station mode: WEP, WPA, WPA2, 802.1x EAP	
Ethernet	10/100/1000 Mbps RJ-45 LAN	
Interface	1 x HDMI, 1x VGA 1 x USB 2.0 Host Type-A 1 x USB 3.0 Host Type-A 1 x USB 3.0 Host Type-C	1 x 3.5mm Audio Jack 1 x 10/100/1000 Ethernet LAN 1 x Power Jack
Power supply	12V 2A	
Net weight	500g	
Dimension	170mm x 104.4mm x 30.5mm (HxWxD)	
Temperature	Operating: 0° – 40° C (32° – 104° F) Storage: -10° – 70° C (14° – 158° F)	

Humidity	Operating: 20 – 80% non-condensing Storage: 10 – 90% non-condensing
Certificate	FCC, CE, NCC, BSMI
Warranty	3 years